trueCABLE Cat6 90-Degree Punch-Down Keystone Jack, Unshielded, White (12-pack)

SL-6EPD90CMPTWHT_12pc CABLING

Unshielded Cat6 RJ45 keystone jack with 90-degree IDC punch-down termination and printed T568A/B color codes. Our standard jack for wall plates and keystone patch panels on Cat6 UTP drops.



OVERVIEW

Category	Cat6 U/UTP keystone jack, component rated
Termination	90-degree punch-down (IDC) with retaining cap
Pack	12 pieces, white

CONDUCTORS

Wire	23-24 AWG solid copper
Insulated conductor diameter	0.86-1.10 mm
Wiring	T568A / T568B printed on side

MATERIALS

Housing	ABS plastic
IDC prongs	Nickel/tin-coated phosphor bronze
RJ45 contacts	Gold plated

PERFORMANCE

Bandwidth	Tested to 500 MHz (FAQ lists 250 MHz rated)
Speed	5G to 295 ft; 10G to 165 ft
PoE	802.3af/at/bt, 4PPoE up to 100 W

COMPLIANCE

Listings	UL Listed, ETL Verified
Standards	ANSI/TIA 568.2-D Cat6
Other	RoHS-2, TAA compliant

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.