smartlife
An IT Solutions Company

DATASHEET

Yealink

T34W



GIGABIT, WI-FI ENABLED IP PHONE WITH FOUR LINES

The Yealink T34W is an entry-level IP phone offering seamless connectivity and a quality visual experience. Equipped with an extra-large color screen, dual-band 5G Wi-Fi, and support for up to 4 lines, the T34W is perfect for small and large office environments alike.

KEY FEATURES

- 2.4" 320 x 240 Color LCD Display
- Built-in Dual Band 2.4G/5G Wi-Fi
- USB 2.0 Port For Wired USB Headsets
- Dual-port Gigabit Ethernet
- PoE Support

T34W PHONE PRODUCT SPECIFICATIONS

Audio Features
- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: G.722
- Narrowband codec: PCMU (G.711A), PCMA(G.711μ), G.729,
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features
- 4 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Built-in dual-band Wi-Fi:
  - Network standard: IEEE802.11a/b/g/n/ac
  - Transmission rate: Up to 433Mbps (dynamic)
  - Frequency range: 2.4GHz/5.0GHz
- USB port (2.0 compliant) for: Yealink wired Bluetooth headsets
- Enhanced DSS Key

Directory
- Loal phonebook up to 1000 entries
- Blacklist
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features
- Busy Lamp Field (BLF), Bridged Line Appearance(BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralized call recording
- Visual voice mail
- Call recording

Display and Indicator
- 2.3" 320 x 240-pixel graphical LCD with backlight
- 16-bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Screensaver
- Power saving

Feature keys
- 4 line keys with LED
- 4 line keys can be programmed up to 12 paperless DSS keys (4-page view)
- 5 features keys: transfer, message, headset, redial, mute, hands-free speakerphone
- 6 navigation keys
- Volume control keys

Interface
- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Other Physical Features
- Color: Classic Grey
- Wall mountable
- External Yealink AC adapter: AC 100~240V input
- Power consumption (PSU): 1.65-2.94W
- Power consumption (PoE): 2.33-3.35W
- Dimension (W*D*H*T): 212 × 186 × 146 × 42 mm
- Operating humidity: 10~95%
- Operating temperature: -10 to +45°C (+14 to 113°F)
- Storage temperature: -30 to +70°C (-22 to +158°F)

Management
- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security
- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication
- OpenVPN, IEEE802.1X, L2TP VPN
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

Package Features
- Package content:
  - Yealink SIP-T34W IP phone
  - Handset with handset cord
  - Ethernet Cable (optional)
  - Stand (not applicable to US wall plate Standard)
  - Quick Start Guide
  - Power Adapter
- Qty/CTN: 10 PCS
- N.W/CTN: 10.286 kg
- G.W/CTN: 11.236 kg
- Giftbox size: 238 × 210 × 103 mm
- Carton Meas: 535 × 443 × 250 mm

Compliance

CE FC REACH ISO 9001 metaswitch

QUESTIONS? CONTACT US TODAY!

Smart Life, LLC

(502) 251-4775

info@smartlifecorp.com

smartlifecorp.com/elevate